

TEMPSEN



monitoring for
Life Science



DS-A-140906 Rev. C

Alpha T50X

Temperature USB PDF Data Logger with
External NTC Sensor




Auto PDF Report with Embedded Data

Automatically generating encrypted PDF format report, no software required to obtain data, embedded raw data allows analyzing report via TempCentre and Cold Chain Cloud.



Repeat Start

Repeat start function enables quick start on site without re-configuration.



Multiple Alarm Ranges

Up to 5 alarm ranges offer precise and intuitive statistics for each configured alarm range.



TempCentre 2 Support

Work with TempCentre 2 desktop software to easily and accurately view, analyze, archive and share data recorded from transport and storage, and achieve 21 CFR 11 compliance.



Extra Long Battery Life

Up to 900 days battery life offers long-term continuous recording possibilities.



Online configuration without software

In support of online configuration without needing to download and install any specific software.



Mark Function

Click Mark button to write in time stamp for events requiring special attention during shipment, up to 9 marks available.

Type	Multi-use
Sensor	Temperature: Interchangeable external NTC Probe (1m)
Memory Capacity	28800 readings
Measurement Range	-50°C...70°C (-58°F...158°F)
Accuracy	±0.5°C / 0.9°F
Resolution	0.1°C / °F
Start Mode	Manual / Auto / Temperature start
Logging Interval	1 minute...2 hours
Logging Mode	Start & Stop / Loop
Alarm Range	High and low alarm / 5 alarm ranges
Battery	3.6V lithium battery
Run Time	900 days
Display	Multi-function LCD <ul style="list-style-type: none"> •OK(√), Alarm(x), Running status •Temperature statistics (max, min, avg) •Limit violation event indication •Duration time of each alarm zone •Mark history •Remaining battery days
Button	Start / Stop / Mark / View
Connection	USB 2.0 Connector
Data Specification	<ul style="list-style-type: none"> •Temperature •Date/Time •Mark
Automatic Data File	Encrypted PDF report with embedded raw data
Software	TempCentre 2 (21 CFR 11 compliant)
Compatible OS	WIN 7 / 8 / 10
Calibration	Factory NIST traceable 3-point calibration
Certifications	CE, DO160G, RoHS
Dimensions	107mm L x 48mm W x 12mm H
Weight	Approx. 75g
Packaging/Material	Case / Polycarbonate
Protection Class	IP54

TempSen Electronics Company, a leading provider of data loggers & data acquisition systems headquartered in Shanghai, China, is committed to continuously offering a broad range of temperature monitoring devices and solutions for food and pharmaceutical industries, helping users employ stringent and effective monitoring measures for temperature sensitive goods in transit and storage. TempSen reserves the right to change any specifications and information about products without prior notice. TempSen, ITAG, Tempod are registered trademarks of TempSen Electronics Company. All other trademarks mentioned herein are property of their respective companies.